# NEW GEN CLEANING FLUIDS



## FORMULA TS-5

A new generation cleaning fluid containing **no** Methylene Cloride and **no** N Propyl Bromide. It will quickly remove grease, oil, dirt, cosmetic stains and Screen Printing inks and soils from all fabrics. It is the ideal replacement for products that are being phased out due to health concerns and has no US ground or air shipping restrictions. FORMULA TS-5 is a volatile spot remover that is profiled as being lower in toxicity than comparable products and has no detectable flash point. The ingredients are not Prop 65 listed and have EPA SNAP approval. FORMULA TS-5 has a high TLV and is not subject to the stringent OSHA monitoring regulations for methylene chloride. Tomorrow's Spot Cleaning fluid, Today!!

1 Gal TS5-1G 4 Gal Case TS5-4G 5 Gal Can TS5-5G 55 Gal Drum TS5-55G



## **PREMIUM 2000**

Premium 2000 is a new generation spot cleaning fluid that will remove grease, oil, dirt and cosmetics along many other industrial and household stains from all textile fabrics. Can be used on apparel, bedding and upholstery and any porous material. PREMIUM 2000 is fast drying and formulated to help eliminate ringing. It does not contain Methylene Chloride, N Propyl Bromide or Perchloroethylene. With a TLV in excess of 200ppm, it is not subject to the stringent OSHA monitoring regulations for methylene chloride. It does not contain any chemicals that require an OSHA cancer warning nor is it Ca. Prop 65 Listed. Premium 2000 has no shipping restrictions and is not considered a flammable liquid. It can be used as a hand spotter or with conventional spot cleaning equipment.

 1 Gal
 P2000-1G
 4 Gal Case
 P2000-4G

 5 Gal Can
 P2000-5G
 55 Gal Drum
 P2000-5G

# FORMULA DT-1000

Removes DTG Inks and DTF Transfers. A new generation cleaning fluid containing **no** Methylene Chloride and **no** N Propyl Bromide. This revolutionary product is the first cleaner developed exclusively to remove DTG printing inks and DTF Transfers. Designed to be sprayed through a Spot Cleaning gun, DT-1000 dissolves virtually all inks and adhesives used in the DTG & DTF processes. It's unique chemistry reduces health concerns and has no US ground or air shipping restrictions. FORMULA DT-1000 is a volatile spot remover that is profiled as being lower in toxicity than comparable products and has no detectable flash point. The ingredients are not Prop 65 listed and have EPA SNAP approval. FORMULA DT-1000 has a high TLV and is not subject to the stringent OSHA monitoring regulations for methylene chloride.

1 Gal DT1000-1G 4 Gal Case DT1000-4G 5 Gal DT1000-5G 55 Gal Drum DT1000-55G



USA:800-564-1096 TEL: 805-965-0704 FAX: 805-963-7794

www.tekmarltd.com ● sales@tekmarltd.com
P.O. Box 4700, Santa Barbara, CA 93140 USA
Warehouses: Santa Barbara CA ● Conyers GA

The Texstyle™ range of cleaning fluids all contain patented additives that actually allow the chemical to penetrate the stain faster and more completely. This speeds up the cleaning process, saves time and money and makes sure that the job is done right the first time. No Redo's, No Residue, No rings, just perfect results every time.



# NEW GEN CLEANING FLUIDS TECHNICAL DATA

PRODUCT	USE	Flashpoint	Hazardous Material	Hazardous Air Pollutant	Restricted Shipping	Cancer Warn-	Health CA Prop 65 Listed	TLV	Primary Active component
				(H.A.P.)		ings	00 2.0.00		component
Formula TS-5	Oil, Grease, Cosmetics Screen Print Inks	None Detected	No	No	No	No	No	200 PPM	Brominated Hydrocarbon
Premium 2000	Oil, Grease Dirt, Cosmetics	None Detected	No	No	No	No	No	200 PPM	Brominated Hydrocarbon
Formula DT-1000	DTG and DTF Transfers	None Detected	No	No	No	No	No	200 PPM	Brominated Hydrocarbon
Formula TS-1	Oil, Grease Dirt, Cosmetics	None Detected		Yes	1 Gallon: <b>LIMITED QUANTITY</b> Larger Sizes: Class 6.1 UN 2810 PG III	Yes	Yes	25-300PPM	Methylene Chloride
Formula TS-3	Screen Print Inks & Adhesives	None Detected	Yes						

#### FORMULA TS-5

Removes grease, oil, dirt, cosmetic stains and Screen printing inks and soils from all fabrics. No Methylene Chloride or NPB

Vapor Pressure 232mm Hg @20°C Flash Point Non Detected <sup>2</sup>

Specific Gravity 1.255 (water = 1) Boiling Point 30-42 ℃

VOC Content: VOC 950 g/l Evaporation Rate (n-butyl acetate =1) >0.68

Appearance: Clear, colorless liquid Kauri-Butanol (KB Value) >115

## PREMIUM 2000

Removes grease, oil, dirt, cosmetic stains and Screen printing inks and soils from all fabrics. No Methylene Chloride or NPB

Vapor Pressure 225mm Hg @20°C Flash Point Non Detected <sup>2</sup>

Specific Gravity 1.220 (water = 1) Boiling Point 30-42 °C

VOC Content: VOC 975 g/l Evaporation Rate (n-butyl acetate =1) >0.64

Appearance: Clear, colorless liquid Kauri-Butanol (KB Value) >110

## DT-1000

Removes DTF and DTG Transfers No Methylene Chloride

Vapor Pressure 232mm Hg @20°C Flash Point Non Detected <sup>2</sup>

Specific Gravity1.255 (water = 1)Boiling Point30-42 °CVOC Content:VOC 950g/lEvaporation Rate (n-butyl acetate = 1)>0.68Appearance:Clear, colorless liquidKauri-Butanol (KB Value)>115

### SHIPPING SPECIFICATIONS

PRODUCT	PACKAGE SIZE	CASE WEIGHT	DIMENSIONS	HARMANIZED TARRIF CODE
Formula TS-5	1 GAL (4x1g) 5 GAL Can 55 Gallon Drum	44lbs (20.00kg) 55lbs (24.54kg) 569lbs (258.63kg)	13" x 10.5" x 12" 12" x 12" x 15" 23" x 23"x 35"	3814.00.5090
PREMIUM 2000	1 GAL (4x1g) 5 GAL Can 55 Gallon Drum	45lbs (20.45kg) 55lbs (25.00kg) 580lbs (263.63kg)	13" x 10.5" x 12" 12" x 12" x 15" 23" x 23"x 35"	3814.00.5090
Formula DT-1000	1 GAL (4x1g) 5 GAL Can 55 Gallon Drum	44 lbs (20.45kg) 55lbs (25.00kg) 569lbs (263.63kg)	13" x 10.5" x 12" 10" x 14" x 16" 23" x 23"x 35"	3814.00.5090



 $<sup>^{\</sup>mathbf{2}}$  Flashpoint tested using ASTM method  $\,$  D-56—Tag Closed Cup Test